

POS Peripherals

Pole Customer Display



Model Name	LCM202J-B-PL	VFD202E-B-PL	VFD202N-B-PL
Fonts / Language	English, French, German, Italian, Swedish, Norwegian, Danish, Spanish	English, French, German, Italian, Swedish, Norwegian, Danish, Spanish, Japanese, Russian, Slavonian	English, French, German, Italian, Swedish, Norwegian, Danish, Spanish, Portuguese, Japanese, Korean, Simple Chinese, Traditional Chinese
User Define Character	Yes	Yes	No
Brightness	150 nits	700 nits	1000 nits
Display Mode	LCD Display (Black & White)	VFD Display (Blue Green)	VFD Display (Blue Green)
Command	EPSON ESC/POS, UTC Standard	EPSON ESC/POS, UTC Standard	EPSON ESC/POS
MTBF	20,000 hours	25,000 hours	25,000 hours
Number of Columns	20 Columns x 2 Lines		
Character Type	5 x 7 dot matrix	5 x 7 dot matrix	15 x 16 dot matrix
Character Size	9.66 x 6.00 mm	9.0 x 5.25 mm	9.0 x 5.25 mm
Power Supply	DC 12V	DC 12V	DC 5V
Interface	RS-232		
Total Height	145~ 585 mm		
Weight	0.83 kg		
View Angle	0~30 degree		
Rotate Angle	270 degree (Max)		
Operating Temperature	0°C ~ 40 °C		
Safety Compliance	CE, FCC, VCCI		

* Note 1 : For OPOS driver, please contact supplier

* Note 2: Powered by system, if you need extra power adapter, please contact supplier.

Specifications are subject to change without notice. Issue Date: 2010 / 07

