



MSR

Part No. : Z0500002

Standard	ANSI/ISO 7810, 7811-1/6, 7813 , 3 Tracks
Direction	Bi-direction with 7~250 cm/s
Interface	PS/2
MTBF	125,000 hours Head 1,000,000 passes



iButton & MSR Module

iButton

Part No. : Z0500005

Specification	Supports decode ID code of all iButtons conforming to Dallas Semiconductor® 1-wire protocol
---------------	---

MSR

Standard	ANSI/ISO 7810, 7811-1/6, 7813 , 3 Tracks
Direction	Bi-direction with 7~250 cm/s
Interface	PS/2
MTBF	125,000 hours Head 1,000,000 passes



RFID & MSR Module

RFID

Part No. : Z0500006

Power Requirements	5 V regulated through USB
Frequency	13.56 MHz
Interface	USB V1.1 compliance or higher
Protocol	GNET PLUS
Card type	Mifare MF1 standard cards for 1024/4096 bytes and Mifare UltraLight cards of EPROM size 512 bits for ISO14443A
Reading distance	0~6 cm
Transponders supported	Read / Write

MSR

Standard	ANSI/ISO 7810, 7811-1/6, 7813 , 3 Tracks
Direction	Bi-direction with 7~250 cm/s
Interface	PS/2
MTBF	125,000 hours Head 1,000,000 passes



Fingerprint & MSR Module

Fingerprint

Part No. : Z0500004

Pixel resolution	512 dpi (average x, y over the scan area)
Scan capture area	14.6 mm (nom. width at center) 18.1 mm (nom. length)
Color bits	8-bit grayscale (256 levels of gray)
Power Requirements	5 V regulated through USB
Interface	USB V1.1 compliance or higher

MSR

Standard	ANSI/ISO 7810, 7811-1/6, 7813 , 3 Tracks
Direction	Bi-direction with 7~250 cm/s
Interface	PS/2
MTBF	125,000 hours Head 1,000,000 passes